

Docs » Views and Templates Category » Content Project » Docs Plugin

Docs Plugin

Documentation management, with a sidebar and nested sections.

Anonymous · 21/10/2026

Docs plugin

Manages documentation pages, nested arbitrarily deep — see [Content hierarchy](#). Renders as HTML, Markdown or PDF depending on the requested format (Accept header, or `.md/.pdf` suffix) — see [PDF and Markdown export](#) for what the last two add, including bundling a whole section into one file with `?full=1`.

Configuration (`services.yaml`)

Enabled under `derafu.content.config.plugins.docs`:

```
parameters:
  derafu.content.config:
    plugins:
      docs:
        path: 'resources/content/docs'
        sidebarDepth: 5
```

Option	Type	Default	Description
<code>path</code>	string	<code>resources/content/docs</code>	Directory scanned for docs, relative to the website root.
<code>include</code>	array of glob patterns	<code>['**.{markdown,md}']</code>	Files considered content, relative to path.
<code>exclude</code>	array of glob patterns	<code>[]</code>	Files excluded even if matched by <code>include</code> .
<code>sidebarPath</code>	bool	<code>true</code>	Whether to show the sidebar, auto-generated from the content hierarchy. There is no support for a custom, manually curated sidebar file — sort/label docs via <code>sidebar_position/sidebar_label</code> in their frontmatter instead.
<code>sidebarCollapsible</code>	bool	<code>true</code>	Whether sidebar categories can be collapsed.
<code>sidebarCollapsed</code>	bool	<code>true</code>	Whether sidebar categories start collapsed.

Option	Type	Default	Description
<code>sidebarDepth</code>	int	5	Maximum nesting depth shown in the sidebar.
<code>showLastUpdateAuthor</code>	bool	true	Whether to show who last updated the doc.
<code>showLastUpdateTime</code>	bool	true	Whether to show when the doc was last updated.
<code>breadcrumbs</code>	bool	true	Whether to show breadcrumbs above the doc.
<code>tags</code>	array of strings, or string	[]	Predefined tags for the docs.
<code>onInlineTags</code>	ignore log warn throw	warn	What to do when a doc uses a tag that isn't in the predefined tags list.

Content frontmatter

Docs use the [generic content frontmatter](#), plus a few fields read directly by the docs template (not part of the shared schema, but supported the same way via arbitrary metadata):

Field	Type	Default	Description
<code>show_title</code>	bool	false	Renders # {title} at the top of the body — useful together with <code>hide_title: true</code> if you want the title placed differently than the default heading.
<code>show_description</code>	bool	false	Renders the <code>description</code> right below the title inside the body.
<code>iframe</code>	string	none	URL embedded as a full-width <code><iframe></code> below the content.
<code>openapi</code>	string	none	URL of an OpenAPI/Swagger spec; renders a full Swagger UI below the content instead of (or in addition to) the Markdown body.
<code>show_source</code>	bool	false	Shows the raw source of the file (Markdown or Twig) in a code block below the content.
<code>show_children</code>	bool	false	Renders a card grid linking to this doc's direct children (title + description), useful for section landing pages.

`hide_table_of_contents` keeps the generic default (false) for this plugin.

Last updated on 21/10/2026