

Pages Plugin

Standalone pages management, rendered as HTML, Markdown, PDF or JSON.

Anonymous · 21/08/2026

Pages plugin

Manages standalone pages (an “about us”, a landing page, changelog, etc.), including `.html.twig` files in addition to Markdown. Same content model and format negotiation (HTML/Markdown/PDF/JSON) as [Docs/FAQ](#), just without a listing/tag view — pages are meant to be linked directly, not browsed.

Route and the `/pages` prefix

Route	Path	Description
pages_page	GET <code>/pages/{uri}</code>	Shows a page. Format negotiated the same way as every other content plugin (Accept header, or <code>.md/.pdf/.json</code> suffix).

The route is registered under `/pages` **on purpose**, not at the root (`/about` instead of `/pages/about`). The `{page: .+}` pattern is a catch-all, and the router tries routes with parameters *before* it tries file-based routes (Derafu\Routing\Parser\FileSystemParser, used for standalone Twig pages placed directly in `templates/pages/` by the website itself, with no content model). A catch-all with no prefix would shadow every one of those file-based pages: the router would never even get to ask the file-system parser about a URI this route already claims, since it checks parsers in order and stops at the first one that matches.

We verified this in practice: with the plugin enabled and content under `resources/content/pages/`, every existing hand-written route (static ones, and file-based ones from `templates/pages/`) kept working exactly as before — only URIs actually starting with `/pages/` are affected.

If a website wants pages at the root anyway, it can register its own route pointing at the same handler instead of importing this one:

```
pages_page:
  path: /{page: .+}
  handler: 'Derafu\Content\Plugin\Pages\PagesController::show'
```

Registering that **before** any route that relies on `FileSystemParser`'s auto-discovery turns this trade-off off for that whole website: from then on, every flat page must be a content item (title/tags/draft/etc. via frontmatter), not a hand-authored Twig template dropped into

`templates/pages/`. Pick one mechanism per website, not both, once this is unprefixed.

Configuration (`services.yaml`)

Enabled under `derafu.content.config.plugins.pages`:

```
parameters:
  derafu.content.config:
    plugins:
      pages:
        path: 'resources/content/pages'
```

Option	Type	Default	Description
<code>path</code>	string	<code>resources/content/pages</code>	Directory scanned for pages, relative to the website root.
<code>include</code>	array of glob patterns	<code>['**.{markdown,md,html.twig}']</code>	Files considered content, relative to <code>path</code> . Unlike other plugins, this also matches <code>.html.twig</code> files.
<code>exclude</code>	array of glob patterns	<code>[]</code>	Files excluded even if matched by <code>include</code> .
<code>showLastUpdateAuthor</code>	bool	<code>false</code>	Whether to show who last updated the page.
<code>showLastUpdateTime</code>	bool	<code>false</code>	Whether to show when the page was last updated.

Content frontmatter

Pages use exactly the [generic content frontmatter](#), nothing added.

Last updated on 21/08/2026