

Development

Development

Anonymous · 20/10/2026

Development

The package renders every example of [Components](#) as a page that opens in a browser, so a component can be seen while it is written.

The Examples

The examples are the files `tests/fixtures/examples/block-*.html.twig`, one per component, with the data that the component can have. The tests render them with the strict mode of Twig in a Symfony kernel. The images they use are in `tests/fixtures/examples/assets`.

The Pages

Running the tests of the examples saves, next to each example, an HTML page with its name:

```
vendor/bin/phpunit --filter ExamplesTest
```

`tests/fixtures/examples/block-alert.html.twig` gives `tests/fixtures/examples/block-alert.html`. The pages are not versioned.

Each page has Bootstrap 5 and Font Awesome 6 from a CDN, the HTML of the component, and a link to `resources/css/components.css` of the package by a relative path, so a change in the CSS is seen by reloading the page. The page opens from the file system.

The Videos

The embeds of YouTube do not load from `file://` (they show the error 153, "Video player configuration error"): they need a page that is served by HTTP. Serve the directory of the package and open the page by its path:

```
php -S localhost:8000
```

`http://localhost:8000/tests/fixtures/examples/block-video.html`.

The Quality of the Code

```
composer phpstan    # PHPStan, level 9.  
composer phpcs      # The code style.  
composer tests      # PHPUnit, with the coverage.
```

Last updated on 20/10/2026